







RoHS
Compliance



SCHEMATIC



PCB LAYOUT



7	BALL	STEEL	1					
5	CONTACT	P B S	2	Ag PLATED	6	SPRING	STEEL WIRE	1
3	TERMINAL	BRASS	8	Ag PLATED	4	TERMINAL BASE	PHENOL RESIN	1
1	FRAME	S P C C	1	Ni PLATED	2	KNOB	P O M	1
NO	PART	MATERIAL	QTY	REMARKS	NO	PART	MATERIAL	QTY
								REMARKS

ISSUED

SPECIFICATION

TITLE: SIDE KNOB SLIDE SWITCH (2P3T)



RATING: DC 30V 0.5A

CONTACT RESISTANCE: 30m Ω max.

INSULATION RESISTANCE: 500M Ω at 500V DC

WITHSTAND VOLTAGE: AC 500V for 1 minute

OPERATION FORCE: REFER ATTACH SPECIFICATION

SWITCHING LIFE: 10K cycles min.

MODEL NO: SK-23H01 (G)

TOLERANCE

UNIT: MM

DWN.

UP TO 1.0: $\pm$ 0.1

SCALE: 2:1

CHK'D.

1.0 TO 10.0: $\pm$ 0.2

VERSION: 01

APPD.

OVER 10.0: $\pm$ 0.3

DRWG NO: